

Specification Standing Seam Panel



Profile	EuroPlus Standing Seam Panel fixed with concealed clips
Material	Choose from available finishes below
Gauge:	Choose an available gauge
Rib Height:	25mm or 38mm
Cover Width Standard:	330mm, 430mm
Cover Width Non-Standard:	250mm -- 530mm
Fixing Method:	Fixed and Sliding clips made of Stainless Steel 0.55 BMT
Roof Installer:	The roof sheeting and wall cladding shall be installed by an accredited Revolution Roofing Installer, in accordance with manufacturer specifications.
Finishes available:	Copper 0.55 BMT or 0.7 BMT Corten 0.7 BMT Painted Aluminium 0.8 BMT PRINTECH Aluminium 0.8 BMT
Substructure Details:	<p>Roof Sheeting: Installed on 19mm plywood substrate, ensuring the joints of the plywood is flush and there is a separation barrier placed between the Standing Seam profile and plywood to avoid condensation issues. The Standing Seam is to have a double locked seam when used as a roofing profile however the profile can be single locked when the pitch of the roof is greater than 15 degrees.</p> <p>Wall Cladding: Installed on plywood substrate, ensuring the joints of the plywood is flush and there is a separation barrier placed between the Standing Seam profile and plywood to avoid condensation issues. Standing Seam only needs to be single locked for a wall cladding application.</p>

For more information please contact :

SA | Shawn Stevens 0428 137 398 | shawn.stevens@revroof.com.au

WA | Greg Harbour 0406 012 099 | greg.harbour@revroof.com.au

Nat | Eric Lien 0448 122 127 | eric.lien@revroof.com.au