



Design and installation to AS1562.1, pre painted and organic film/metal laminate products: to AS2728	
Profile	Concealed Fixed EuroPlus Flat Lock Panel fixed with concealed clips
Material	Choose from available finishes below
Gauge:	Choose an available gauge
Finish:	Colour as per Colour Schedule
Fixing Method:	Concealed fix clips made of Zinalume 0.55 BMT
Fasteners:	Timber 10-12 x 25mm wafer head Type 17 self-drilling screws. Steel 10-24 x 22 Wafer Cross recess Tekes (steel)
Installer:	Wall cladding to be installed by an accredited Revolution Roofing installer in accordance with manufacturer specifications.
Cover Width Standard:	310mm, 410mm or 485mm
Cover Width Non-Standard:	130mm -- 525mm
Finishes available:	Heritage Galvanised Z600 G300 0.55 BMT Colorbond® AM100 G300 0.55 BMT or 0.8 BMT Colorbond® Matt Finish AM100 G300 0.55 BMT Colorbond® ULTRA AM150 G300 0.55 BMT Colorbond® METALLIC AM100 G300 0.55 BMT Copper 0.55 BMT or 0.7 BMT Corten 0.7 BMT Painted Aluminium 0.8 BMT PRINTECH Aluminium 0.8 BMT
Substructure Details:	Flat Lock Panel to be installed on a plywood substrate, ensuring the joints of the plywood is flush and there is a separation barrier placed between the Flat Lock Panel and the plywood to avoid condensation issues.
Installation:	Wall Cladding: Flat Lock Panels should be installed with concealed clips spaced for 3 per lineal metre.