

Warranty Terms

RESIDENTIAL, COMMERCIAL AND LIGHT INDUSTRIAL BUILDINGS WARRANTY FOR THE AUSTRALIAN MARKET



RevZINC™ AM125 alloy-coated metal products used in the manufacture of residential, commercial and light industrial buildings for atmospheric category ISO1-3 Mild & ISO3 Moderate will perform as follows:

Area	Application	Warranty Period
		Perforation
Residential Commercial Light Industrial	Roof (over 1 km from Marine & industrial environment)	Up to 30 Years
	Wall (over 1 km from Marine & industrial environment)	Up to 15 Years
Rain Water Goods	Gutters, Downpipes and Fascia (over 1 km from Marine & industrial environment)	Up to 12 Years

The product/s covered under this warranty are subject to normal wear and tear, which may include dirt collection. Evidence of white corrosion may appear at unwashed tension bends or cut edges. This is a natural consequence of weathering and does not constitute a failure of the coating system. Testing to determine coating performance will be in accordance with the methods described in Australian Standard AS1580.

If any RevZINC™ AM125 product fails to perform as warranted, we will, at our sole option, repair or replace (excluding labour) the affected material.

Please note, this warranty is subject to the following terms and conditions:

- This warranty will not apply to weather, over time as a result of normal wear and tear.
 - If the RevZINC™ AM125 product has not been maintained in accordance with the published recommendations of Revolution Roofing and accepted good trade practices, this warranty will not apply.
 - To maintain warranty status and avoid mismatching of appearance, do not mix RevZINC™ AM125 steel with other alloy-coated steel products in any one application or plane. For further clarification please contact Revolution Roofing.
 - If inappropriate fastenings are used or incorrectly installed, this warranty will not apply.
 - Revolution Roofing must be given the opportunity for inspection on site prior to any remedial action being offered or taken.
 - The product must be manufactured from prime RevZINC™ AM125 metal products and in no way be coated with post-painted treatments.
 - All products installed in sheltered areas, or in areas unwashed by rain exposure, must be regularly washed down in accordance with published maintenance requirements by Revolution Roofing as detailed below.
 - RevZINC™ AM125 Steel must not be used as concrete framework or be immersed during construction.
 - Damage or corrosion resulting from the following are not covered by this warranty.
 1. Damage sustained during or after installation.
 2. Damage sustained as a result of contact with concrete, mortar, bitumen, soils, ashes, fertilisers or other moisture retaining substances.
 3. Deterioration of the sheet caused by contact with green, wet or treated timbers.
 4. Areas in metallic contact with lead or copper or subject to the run-off from lead or copper flashing and pipes.
 5. Deterioration of sheet as a result of white corrosion, paint blistering or red rust.
 6. Coating failure as a result of standing water, or "ponding water".
 7. Failure to remove debris leading to the accumulation of moisture retaining matter in gutters and downpipes.
 8. Chemical attack including sunscreen, creams or oils, weed killer, fumes or other corrosive liquids.
 9. Collapse or movement of the structure on which the roof is mounted or any removal or weakening of the roof's supports or foundations.
 - 10. Failure to comply with the Maintenance requirements.
 - 11. Corrosion from the underside of the RevZINC™ AM125 material, as a result of high humidity, condensation or pollution from within the building.
 - 12. Incorporation of the RevZINC™ AM125 product into, or use in connection with, roofing or cladding materials manufactured by someone other than the supplier as directed by Revolution Roofing.
 - 13. The installed pitch of the roof must be equal to or greater than the minimum recommended for the profile used.
 - 14. Causes after the product has left our control, including immersion as a result of flood or sub standard site draining, storm and tempest or other acts of God.
 - 15. Corrosion arising from lapped areas of end-lapped sheets.
- RevZINC™ AM125 Steel must be installed in strict accordance with, in order of preference, all applicable industry standards and the Building Code of Australia current at the date of installation, including SA HB 39:2015. In the case where no standard applies, RevZINC™ AM125 material must be installed in strict accordance with the manufacturer's published installation guidelines, current at the time of installation.
- Revolution Roofing and the steel manufacturer reserve the right to inspect a building prior to issuing of the warranty and/or to inspect and conduct tests as necessary at any time after a claim is made under this warranty and accordingly have access to the property.
- Our liability under this warranty shall in all cases be limited to replacing or repairing the defective product as specified above (excluding labour). Any repaired or replaced product will be covered by this warranty only for the unexpired portion of the warranty on the original product. Revolution Roofing will not under any circumstances be liable for consequential loss or damage. All claims must be made promptly in writing and accompanied by the original warranty document. This warranty does not in any way affect the rights of a consumer under the Consumer Guarantees Act.
- Minimum Maintenance Requirements**
1. Washing of naturally unwashed areas every 6 months.
 2. Removal of debris from gutters every 6 months.
 3. Any noticeable build up of salt deposits and/or other contaminants are removed when identified.
 4. Inspection of the roof, including fasteners to repair any damage, every 6 months.
- Note: This document is an example only.** Specific warranty periods are determined by Revolution Roofing and may vary according to location and design. To obtain a site specific warranty, please visit revolutionroofing.com.au