


Rev 5 Plus

A ROBUST ROOFING AND WALLING PROFILE THAT COMPLEMENTS ANY COMMERCIAL AND INDUSTRIAL APPLICATION DUE TO ITS STRENGTH. IT ALSO DELIVERS EXCEPTIONAL SPANS FOR CARPORTS & VERANDAHS.



REV 5 PLUS FEATURES & BENEFITS

- 33% larger rib
- 35% greater water carrying capacity
- 25% stronger
- Internal roof span based on 0.42mm BMT exceeds all other equivalent profiles that are formed on a trapezoidal profile based on 0.42mm and some 0.48mm BMT
- Internal roof span based on 0.42mm BMT exceeds all other profiles that are equivalent to Rev-Klip 0.42mm and some 0.48mm BMT, eliminating the additional costs associated to the concealed fix clip and down gauging BMT
- Robust profile for roofing and walling application
- Capability to go down to a minimum 2 degree roof pitch
- Available gauges based on 0.42mm BMT and 0.48mm BMT G550
- Available in RevZinc AM125
- Product compliant with AS 1562.1 1992 and AS 4040 — 1992
- Exclusive to Revolution Roofing



(ROOF SPAN TABLE - 0.42MM)

Profile	Internal	End	Single
Rev 5 Plus (36mm)	2350	1750	1250
Rev 5 (27mm)	2000	1600	1000

(ROOF SPAN TABLE - 0.48MM)

Profile	Internal	End	Single
Rev 5 Plus (36mm)	2950	2250	1600
Rev 5 (27mm)	2750	2000	1600

Available in 22 standard colours, plus 7 matt finishes. Ask us about custom colours.