



Design and installation to AS1562.1, prepainted and organic film/metal laminate products: to AS2728.		
Profile	EuroPlus Interlocking Panel	
Material	Choose from available finishes below	
Gauge	Choose an available gauge	
Finish	Colours as per Colour Schedule and Availability	
Fixing Method	Positively fixed using a wafer head screw	
Fasteners	Timber 10-12 x 25mm wafer head Type 17 self-drilling screws Steel 10-24 x 22 Wafer Cross recess Teks (steel)	
Depth	25mm	
Panel Cover	(Min 185mm – max 300mm)	
Recess Joint Width	(0mm, 5mm, 10mm, 15mm)	
Installer	The wall cladding shall be installed by an accredited Revolution Roofing Installer, in accordance with manufacturer specifications.	
Finishes available	NextSTAR™ 0.55 BMT	Metallic 0.55 BMT
	NextSTAR™ Ultra 0.55 BMT	Matt Finish 0.55 BMT
	NextREME™ XC (PVDF+Alu)	Heritage Galvanised
	NextREME™ SE (SMP+Alu)	Raw Steel / Corten 0.77mm
	Copper 0.7mm	
Substructure Details	To be installed using nominated fasteners on plywood or battens with an internal span and end span of no greater than 600mm.	