



Design and installation to AS1562.1, prepainted and organic film/metal laminate products: to AS2728.		
Profile	EuroPlus Interlocking Panel	
Material	Choose from materials below	
Gauge	Steel 0.55, Steel 0.80, Aluminium 0.8, Corten 0.7, Copper 0.7, Stainless Steel 0.55	
Colour	Refer Finishes Schedule	
Fixing Method	Concealed Pierce Fixing	
Suitable Fasteners Steel	10g –16 x 16mm Wafer Head, 10g –12 x 16 Hex Head Fastener	
Suitable Fasteners Timber	10g –12 x 25 Hex Head Type 17, 10g – 12 x 25mm Wafer Head Type 17	
Suitable Fasteners Plywood	10g – 12 x 25 Hex Head Type 17, 10g – 12 x 25mm Wafer Head Type 17	
Fasteners for Copper, Corten, Stainless	Stainless 10g – 16 x 25 Wafer Head	
Panel Depth	25mm	
Standard Cover	200mm, 250mm, 300mm	
Cover Available	185mm – 400mm	
Finishes available	NextONE™	NextSTAR™
	Matt Finish	Pastel
	Metallic	NextSTAR™ Ultra
	NextFACTOR™ XL	NextREME™ SE
	NextREME™ XC	NextCHROMATIC™
	Copper	Corten
	Stainless Steel	
Substructure Details	Metal Batten, Timber Batten, Plywood	
Installation Instructions	Refer EuroPlus Installation Advice document	

