

## SPECIFICATIONS SHEET SnapLock Panel



Design and installation to AS1562.1, prepainted and organic film/metal laminate products: to AS2728.		
Profile	EuroPlus SnapLock Panel	
Material	Choose from materials below	
Gauge	Steel 0.55, Aluminium 0.8	
Colour	Refer Finishes Schedule	
Fixing Method	Concealed Fixed Clips	
Suitable Fasteners   Steel	10g – 15 x16mm needle point flat head, 10g –16 x 16mm Wafer Head	
Suitable Fasteners   Timber	10g - 12 x 25 flat head Type 17, 10g - 12 x 45mm Wafer Head	
Suitable Fasteners   Plywood	10g –12 x 25 Flat Type Head Type 17, 10g –12 x 25mm Wafer Head	
Rib Height	25mm	
Standard Cover	265mm, 350mm	
Cover available	185mm – 465mm	
Finishes available	NextONE™	NextSTAR™
	Matt Finish	Pastel
	Metallic	NextSTAR™ Ultra
	NextFACTOR™ XL	NextREME™ SE
	NextREME™ XC	NextCHROMATIC™
Substructure Details	Metal Batten, Timber Batten, Plywood	
Installation Instructions	Refer EuroPlus Installation Advice document	



