

CUSTOMER

Order no:	Date ordered:
Contact name and number:	Date required:
Delivery address:	
Project name:	
Materials (select one):	NextCHROMATIC
NextSTAR 0.55 BMT	Metallic 0.55 BMT
NextSTAR Ultra 0.55 BMT	Matt Finish 0.55 BMT
NextREME XC (Aluminium + PVDF) Pastel Series	
NextREME SE (Aluminium + SMP) RawSteel/Corten 0.7mm	
Nexteel Commercial Grade 0.8 BMT Copper 0.7mm	
Colour:	Gauge:
Cover:	
Recess:	
0mm 5mm	10mm 15mm
FASTENER T	

ORDER FORM



CUTTING LIST Cover Quantity Length of Stop Ends Panel (mm) Required **✓**

Maximum Length: 6m.

• Minimum Length: 0.4m.

Coil must be forward ordered: Lead times apply.

Production lead time: 3-5 working days.

Oil Canning is an inherent characteristic of non-ferrous metals with broad flat areas. The Architect, Builder, and Homeowner needs to be aware that oil canning may affect the overall aesthetic outcome. There are measures that can be taken during design and installation to minimise the risk of oil canning such as ensuring the plywood is flush, the panels are fixed vertically, limiting the continuous length of each panel, and reducing the size of the pan. For more information please go to our website, www.revolutionroofing.com.au

revolutionroofing.com.au

Regency Park HQ 5-17 Taminga St Regency Park SA 5010 08 8352 0911 Plympton Sales & Display Centre 576 Marion Rd (cnr Bray St) Plympton SA 5038 08 8352 0990 Southern Branch 14 Bredbo St Lonsdale SA 5160 P 08 8186 0545 Osborne Park 55b Hector St Osborne Park WA 6017 08 9217 9011

