

ORDER FORM

STANDING SEAM

CUSTOMER		CUTTING LIST		
Order no:	Date ordered:	Pan Width	Quantity	Length (mm)
Contact name and number:	Date required:			
Delivery address:				
Project name:				
Materials (select one): *Painted Steel produ	icts to be installed as single lock Standing Seam only. Metallic 0.55 BMT*			
NextSTAR Ultra 0.55 BMT*	Matt Finish 0.55 BMT*			
NextREME XC (Aluminium + PVI				
NextREME SE (Aluminium + SM				
Copper 0.7mm	NextCHROMATIC			
Соррег о./ппп	INEXICHNOMATIC			
Colour:				
Rib height:				
25mm 38mm	m			
Pan width:				
330mm 430n	nm			
Custommm	n (Min 230 Max 530)			
Clips required:				
Sliding	Fixed			
SINGLE LOCK	DOUBLE LOCK			

Oil Canning is an inherent characteristic of non-ferrous metals with broad flat areas. The Architect, Builder, and Homeowner needs to be aware that oil canning may affect the overall aesthetic outcome. There are measures that can be taken during design and installation to minimise the risk of oil canning such as ensuring the plywood is flush, the panels are fixed vertically, limiting the continuous length of each panel, and reducing the size of the pan. For more information please go to our website, www.revolutionroofing.com.au

WIDTH



