




CUSTOMER

Order no:	Date ordered:
Contact name and number:	Date required:
Delivery address:	
Project name:	
Materials (select one): <i>*Painted Steel products to be installed as single lock Standing Seam only.</i>	
<input type="checkbox"/> NextSTAR 0.55 BMT*	<input type="checkbox"/> Metallic 0.55 BMT*
<input type="checkbox"/> NextSTAR Ultra 0.55 BMT*	<input type="checkbox"/> Matt Finish 0.55 BMT*
<input type="checkbox"/> NextREME XC (Aluminium + PVDF)	<input type="checkbox"/> Heritage Galvanised*
<input type="checkbox"/> NextREME SE (Aluminium + SMP)	<input type="checkbox"/> RawSteel /Corten 0.7mm*
<input type="checkbox"/> Copper 0.7mm	
Colour:	
Rib height:	
<input type="checkbox"/> 25mm	<input type="checkbox"/> 38mm
Pan width:	
<input type="checkbox"/> 330mm	<input type="checkbox"/> 430mm
<input type="checkbox"/> Custom _____ mm (Min 230 Max 530)	
Clips (box of 50) quantity required:	
Sliding _____	Fixed _____

CUTTING LIST

[illegible]

- Maximum Length: 8m.
- Minimum Length: 0.6m.
- Coil must be forward ordered: Lead times apply.
- Production lead time: 3-5 working days.

Oil Canning is an inherent characteristic of non-ferrous metals with broad flat areas. The Architect, Builder, and Homeowner needs to be aware that oil canning may affect the overall aesthetic outcome. There are measures that can be taken during design and installation to minimise the risk of oil canning such as ensuring the plywood is flush, the panels are fixed vertically, limiting the continuous length of each panel, and reducing the size of the pan. For more information please go to our website. www.revolutionroofing.com.au

revolutionroofing.com.au

Regency Park HQ
5-17 Taminga St
Regency Park
SA 5010
P 08 8352 0911

**Plympton Sales &
Display Centre**
576 Marion Rd (cnr Bray St)
Plympton SA 5038
P 08 8352 0990

Southern Branch
14 Bredbo St
Lonsdale
SA 5160
P 08 8186 0545

Osborne Park
55b Hector St
Osborne Park
WA 6017
P 08 9217 9011

